

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  

---

please do not report the images to the  
Image Problem Mailbox.



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
| 09/833,397      | 04/11/2001  | Hajime Kimura        | 07977/273001/US4846 | 3430             |

26171 7590 10/06/2003

FISH & RICHARDSON P.C.  
1425 K STREET, N.W.  
11TH FLOOR  
WASHINGTON, DC 20005-3500

EXAMINER

ZEADE, BERTRAND

| ART UNIT | PAPER NUMBER |
|----------|--------------|
|----------|--------------|

2875

DATE MAILED: 10/06/2003

Please find below and/or attached an Office communication concerning this application or proceeding.

RP

# Office Action Summary

Application No.

09/833,397

Applicant(s)

KIMURA ET AL.

Examiner

Bertrand Zeade

Art Unit

2875

-- The MAILING DATE of this communication appears on the cover sheet with the corresponding address --

## Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

## Status

- 1) ☒ Responsive to communication(s) filed on 11 July 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

## Disposition of Claims

- 4) ☒ Claim(s) 1-32 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-21, 23-29, 31 and 32 is/are rejected.
- 7) ☒ Claim(s) 22 and 30 is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

## Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- 11) ☐ The proposed drawing correction filed on \_\_\_\_\_ is: a) ☐ approved b) ☐ disapproved by the Examiner.  
If approved, corrected drawings are required in reply to this Office action.
- 12) ☐ The oath or declaration is objected to by the Examiner.

## Priority under 35 U.S.C. §§ 119 and 120

- 13) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  
a) ☒ All b) ☐ Some \* c) ☐ None of:  
1. ☒ Certified copies of the priority documents have been received.  
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.  
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).  
\* See the attached detailed Office action for a list of the certified copies not received.
- 14) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application).  
a) ☐ The translation of the foreign language provisional application has been received.
- 15) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121.

## Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892) 4) ☐ Interview Summary (PTO-413) Paper No(s). \_\_\_\_\_
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948) 5) ☐ Notice of Informal Patent Application (PTO-152)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449) Paper No(s) \_\_\_\_\_ 6) ☐ Other: \_\_\_\_\_

Art Unit: 2875

## DETAILED ACTION

### *Response to Arguments*

1. Applicant's arguments with respect to claims 1- have been considered but are moot in view of the new ground(s) of rejection.

### ***Claim Rejections - 35 USC § 102***

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

3. Claims 1, 3-7, 9-14, 16 are rejected under 35 U.S.C. 102(e) as being anticipated by Tanaka et al. (U.S.6474826).

Tanaka ('826) discloses a light apparatus having:

Regarding claim 1, a light guiding plate (20) having an upper surface for emitting a first, a first side surface and the second side surface, wherein the upper surface is perpendicular to the first side surface and a second side surface (see fig. 1); a point light source or LED (40) facing an intersection of the first side surface and the second side surface (see figs. 13-15); a reflector member (50) for reflecting a light of the point light source (21), wherein the reflected by

Art Unit: 2875

the reflecting member (50) is incident on at least the first side surface and second side surface of the guiding plate (20).

Regarding claim 3, a prism (22) having a triangular cross-section is provided on upper surface or a lower surface of the light guiding plate (see figs. 1-2 ).

Regarding claim 4, a projection having a rectangular cross-section is provided on an upper surface or the lower surface of the light guiding plate (see figs1, 18-19).

Regarding claim 5, a reflecting plate (50) is provided below the light guiding plate (20).

Regarding claim 6, a light guiding plate (20) having an upper surface for emitting a light, a first side surface and a second side surface perpendicular to the first side surface and the second side surface; and a point light source (40) adjacent to the first side surface, an intersection of the first side surface and the second side surface (see figs. 1), wherein a light emitted from the point light source (40) is incident on the first side surface and the second side surface of the light guiding plate (see figs. 13-15).

Regarding claim 7, the point light source (40) is surrounded by a reflecting member (50), the first side surface, and the second side surface (see fig. 5).

Regarding claim 9, prism (22) having a triangular cross-section is provided on upper surface or a lower surface of the light guiding plate (20).

Regarding claim 10, a projection having a rectangular cross-section is provided on an upper surface or the lower surface of the light guiding plate (see 1, 18-19).

Art Unit: 2875

Regarding claim 11, a reflecting plate (50) is provided below the light guiding plate (20).

Regarding claim 12, as shown in (fig. 1) a light guiding plate (20) having a first side surface (12), a second side surface (21), and a third side surface (10); wherein the first side surface is not perpendicular to the second side surface and the third side surface; and a light source (40) adjacent to the first side surface (12), wherein a light emitted from the light source (40) is incident on the first side surface (12) of the light guiding plate (20) and exits through an upper surface or a lower surface of the light guiding plate (20).

Regarding claim 13, the light source (40) is surrounded with a first reflecting plate (50) and the first side surface (see fig. 1, 5).

Regarding claim 14, a reflecting plate (50) is provided so as to surround side surfaces and a lower surface of the light guiding plate (20), (see fig. 5).

Regarding claim 16, a projection having a rectangular cross-section is provided on an upper surface or the lower surface of the light guiding plate (see 1, 8-9).

Claims 17-18, 21, 23-24, 27-28 are rejected under 35 U.S.C. 103(a) as being patentable over Maegawa et al. (U.S.4,954,930) in view of Fukiharu ('687).

Maegawa ('930) discloses illumination light guide having:

Art Unit: 2875

Regarding claim 17, a first light guiding plate (4) having a first side surface and a second side surface perpendicular to the first side surface; a second light guiding plate (2a) having a first side surface, an upper surface, and lower surface, the upper surface and the lower surface being perpendicular to the first surface (see figs. 1-5 ), wherein the second light guiding plate (2a) is not in contact with the first light guiding plate (4); and a light source (9), wherein the light emitted from the light source (9) is incident on a first surface of the first light guiding plate (4) and exit through a second side surface of the first light guiding plate (4), and wherein the light exiting through the second side surface of the first light guiding plate (4) is incident on the first side surface of the second light guiding plate (2a), and exit through the upper surface or the lower surface of the second light guiding plate (2a).

Regarding claim 18, the first light guiding plate (4) has a shape of rectangular prism (see fig. 1-5).

Regarding claim 21, a first light guiding plate (4) having a first side surface and a second side surface perpendicular to the first side surface; a second light guiding plate (2a) having a first side surface, an upper surface, and a lower surface, the upper surface and the lower surface being perpendicular to the first surface; and a light source (9), wherein the light emitted from the light source (9) is incident on a first surface of the first light guiding plate (4) and exit through a second side surface of the first light guiding plate (4), and wherein the light exiting through the second side surface

Art Unit: 2875

of the first light guiding plate is incident on the first side surface of the second light guiding plate (2a), and exit through the upper surface or the lower surface of the second light guiding plate (2a).

Regarding claim 23, a liquid crystal panel or illuminating portion (2a or 2b or 2c) including a first substrate , a second substrate, and interposed therebetween (see figs. 1-5); an illumination apparatus (2a-2d) adjacent to the liquid crystal panel or illuminating portion (2c) for illuminating an image display plane of the liquid crystal panel (see fig. 1-5), the illumination apparatus including: a first light guiding plate (4) having a first side surface and a second side surface perpendicular to the first side surface; a second light guiding plate (2a) having a first side surface, an upper surface, and lower surface, the upper surface and the lower surface being perpendicular to the first surface (see figs. 1-5), wherein the second light guiding plate (2a) is not in contact with the first light guiding plate (4); and a light source (9), wherein the light emitted from the light source (9) is incident on a first surface of the first light guiding plate (4) and exit through a second side surface of the first light guiding plate (4), and wherein the light exiting through the second side surface of the first light guiding plate (4) is incident on the first side surface of the second light guiding plate (2a), and exit through the upper surface or the lower surface of the second light guiding plate (2a).

Regarding claim 24, the first light guiding plate (4) has a shape of rectangular prism (see fig. 1-5 and abstract).



Art Unit: 2875

Maegawa ('930) does not disclose a point light source.

Fukiharu ('687) discloses a reflection illumination device for object to be illuminated having:

Regarding claims 17, 21, 23, a point light source (16) adjacent to an intersection of the first side surface and the second side surface (see figs. 1-2).

Regarding claim 27, the liquid crystal display or illumination portion (10) device is a transmission type LCD device.

Regarding claim 28, the LCD device or illumination portion (10) is incorporated in one selected from the group consisting of a personal computer, digital camera, a mobile telephone, a video camera, and a car navigation system well known to those skilled in the art.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to utilize the illumination light guide of Maegawa ('930) with the point light source disclosed by Fukiharu ('687) for the benefit and advantage to provide a reflection illumination device for an object to be illuminated, which can obtain high quality display by preventing external light reflected by the surface of a light guide from entering the eyes of a user, because there is provided a reflection illumination device including a light guide place in front of an object to be illuminated, a light source arranged around the light guide, and a reflecting member placed behind the object, and

Art Unit: 2875

serving to totally reflect light emitted from the light source toward the object are formed and arranged on a surface of the light guide.

Claims 29-32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hoshi (U.S.6020944) in view of Fukiharu (U.S.6,435,687).

Regarding claim 29, Hoshi ('944) discloses an illumination device and LCD apparatus including same having: a liquid crystal panel (15) including a first substrate (12), a second substrate (22), and a LCD (15) interposed therebetween; an illumination apparatus (26) adjacent to the liquid crystal panel (15) for illuminating an image display plane of the liquid crystal panel (15), the illumination apparatus (26) including: a first light guiding plate (21) having a first side surface and a second side surface perpendicular to the first side surface; a second light guiding plate (31) having a first side surface, an upper surface, and lower surface, the upper surface and the lower surface being perpendicular to the first surface (see figs. 1-20); wherein the first light guiding plate (21) has a larger refractive index than the second light guide plate (31); and a light source (26), wherein the light emitted from the light source (26) is incident on a first surface of the first light guiding plate (21) and exit through a second side surface of the first light guiding plate (31), and wherein the light exiting through the second side surface of the first light guiding plate (21) is incident on the first side surface of the

Art Unit: 2875

second light guiding plate (31), and exit through the upper surface or the lower surface of the second light guiding plate (2a).

Regarding claim 31, the liquid crystal display device is a transmission type LCD device (see figs. 1-22).

Regarding claim 32, the LCD device is incorporated in one selected from the group consisting of a personal computer, digital camera, a mobile telephone, a video camera, and a car navigation system well known to those skilled in the art.

Hoshi ('944) does not disclose a point light source.

Fukiharu ('687) discloses a reflection illumination device for object to be illuminated having:

Regarding claim 29, a point light source (16).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to utilize the illumination device and LCD apparatus including same of Hoshi ('944) with the point light source disclosed by Fukiharu ('687) for the benefit and advantage to provide a reflection illumination device for an object to be illuminated, which can obtain high quality display by preventing external light reflected by the surface of a light guide from entering the eyes of a user, because there is provided a reflection illumination device including a light guide place in front of an object to be illuminated, a light source arranged around the light guide, and a reflecting

Art Unit: 2875

member placed behind the object, and serving to totally reflect light emitted from the light source toward the object are formed and arranged on a surface of the light guide.

1. Claims 2, 8, 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Tanaka in view of Hoshi (U.S.6,020,944).

Regarding claims 2, 8, 15, Tanaka ('826) discloses the claimed invention except for the ink dot.

Hoshi ('944) discloses an illumination device and LCD apparatus including same having:

Regarding claims 2, 8, 15, an ink dot or pixel (13) is provided on an upper surface or a lower surface of the light guiding plate or light guiding member (21).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to utilize the lighting apparatus of Tanaka (826) with the ink dot disclosed by Hoshi ('944) in order to provide an illumination device having a reflection-type LCD is expected to realize a high resolution display apparatus including a large number of pixels, because of a high aperture ratio allowing a high-density pixel arrangement.

Art Unit: 2875

2. Claims 19-20 and 25-26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Maegawa ('930) in view of Fukiharu ('687) as applied to claims 17 and 23 above, and further in view of Hoshi ('944).

Regarding claim 19, ink dots or pixel (13) are provided on a side surface opposite to the first side surface of the first light guiding plate or liguiding member (21)

Regarding claim 20, ink dots or pixel (13) are provided at a lower density as closer towards the light source (26).

Regarding claim 25, ink dots or pixel (13) are provided on a side surface opposite to the first side surface of the first light guiding plate or liguiding member (21).

Regarding claim 26, ink dots or pixel (13) are provided at a lower density as closer towards the light source (26).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to utilize the Maegawa ('930) in view of Fukiharu ('687) with the ink dot disclosed by Hoshi ('944) in order to provide an illumination device having a reflection-type LCD is expected to realize a high resolution display apparatus including a large number of pixels, because of a high aperture ratio allowing a high-density pixel arrangement.

Art Unit: 2875

***Allowable Subject Matter***

Claims 22 and 30 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

The following is a statement of reasons for the indication of allowable subject matter: The prior art of record neither disclose nor teach a refractive index of a light guide plate which is between 1.8 and 3.0; 1.4 and 1.6.


***Contact Information***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Bertrand BZeade whose telephone number is 703-308-6084. The examiner can normally be reached on 8:00 AM-5:00PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sandra O'Shea can be reached on 703-305-4939. The fax phone number for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703-308-0956.

Bertrand BZeade  
Examiner  
Art Unit 2875

  
Sandra O'Shea  
Supervisory Patent Examiner  
Technology Center 2800